

An LTAG Fragment for German

Hands-on Experience with XMG

Timm Lichte, Wolfgang Maier
Universität Tübingen

June 22, 2007

- ① state of affairs: theory and implementation
- ② extending XMG for MCTAG
- ③ XMG in action: tree fragments, colors, semantic dimension

- **Theory:**

Syntax: free word order (scrambling), coherent constructions

Semantics: underspecified flat semantics on the derivation tree

- **Implementation:**


Preparatory work (extension of XMG)

Implementation of some basic constructions

TAG for English

Fixed complement order in English:

- (1) Peter repairs the fridge. \neq The fridge repairs Peter.



German syntax is flexible


- (1) dass Peter den Kühlschrank heute repariert
dass den Kühlschrank Peter heute repariert
...
('that Peter repairs the fridge today')

- ⇒ linguistically sound analysis using TAG?
- ⇒ desire to abstract away from word order
- ⇒ Multi-Component TAG (MCTAG)

An MCTAG for German

- (2) dass den Kühlschrank Peter heute repariert
('that Peter repairs the fridge today')

- Vector MCTAG (Rambow, 1994):




- MCTAG with shared nodes (Kallmeyer, 2005)
- MCTAG with tuples (Lichte, 2007)

An MCTAG for German

- (2) dass den Kühlschrank Peter heute repariert
('that Peter repairs the fridge today')

- Vector MCTAG (Rambow,1994):
- MCTAG with shared nodes (Kallmeyer,2005)




- MCTAG with tuples (Lichte, 2007)

An MCTAG for German

- (2) dass **den Kühlschrank** Peter heute repariert
('that Peter repairs the fridge today')


- Vector MCTAG (Rambow,1994):
- MCTAG with shared nodes (Kallmeyer,2005)
- MCTAG with tuples (Lichte, 2007)



The formalism of choice: TT-MCTAG


(3) dass des Verbrechens der Detektiv den Verdächtigen dem Klienten |
zu überführen versprochen hat

('that the detective has promised the client to indict the suspect of
the crime')




The formalism of choice: TT-MCTAG

- (3) dass des Verbrechens der Detektiv den Verdächtigen dem Klienten |
zu überführen versprochen hat
('that the detective has promised the client to indict the suspect of
the crime')




The formalism of choice: TT-MCTAG

- (4) dass des Verbrechens der Detektiv den Verdächtigen dem Klienten |
zu überführen versprochen hat
('that the detective has promised the client to indict the suspect of
the crime')





TAG, MCTAG and XMG

- Until January 2007: XMG compiler only for standard TAG, no support for tree sets as present in MCTAG and its variants
- A Metagrammar looked like this:



Extending XMG for TT-MCTAG

- We use (TT-)MCTAG for our German grammar fragment
- XMG should allow for descriptions of sets/tuples, like



~ Extension of the compiler!
(Joint work with Yannick Parmentier)

Explicit specification of sets

- To deal with sets, we would need to extend the XMG description language
- Core parts of the compiler would have to be touched


↪ **lack of generality**

Specification of tree sets



Introduce a different solver module S_3

- No root uniqueness constraint
- Two nodes of a model can be in different trees
- New keyword setvalue

Example:



\rightsquigarrow



Drawbacks and Advantages


Drawbacks (?)

- Unmarked TT-MCTAG head tree
- (So far) no colors available

Advantages


- Different solvers (S_1, S_3) applicable on the same grammar via different axiom definitions
- Maintained flexibility: Other solvers can be integrated
- XMG for MCTAG has wider range of potential users

An example




- Class Vn1 (intransitive verbs) uses all of the above trees:

An example




- Class Vn1 (intransitive verbs) uses all of the above trees:
 - V12base: Vorfeld + Mittelfeld
 - V3base: Mittelfeld
 - VerbArgumentNoun

An example




- Class Vn1 (intransitive verbs) uses all of the above trees:
 - V12base: Vorfeld + Mittelfeld
 - V3base: Mittelfeld
 - VerbArgumentNoun
- Case feature of NP is exported

An example




- Class `Vn1` (intransitive verbs) uses all of the above trees:
 - `V12base`: Vorfeld + Mittelfeld
 - `V3base`: Mittelfeld
 - `VerbArgumentNoun`
- Case feature of NP is exported
- Call `setvalue Vn1`. Result:

An example



- Class `Vn1` (intransitive verbs) uses all of the above trees:
 - V12base: Vorfeld + Mittelfeld
 - V3base: Mittelfeld
 - VerbArgumentNoun
- Case feature of NP is exported
- Call `setvalue Vn1`. Result:



(V3)

(V1/V2)

- The modified compiler is available in the XMG subversion repository (branch XMG-TUEBINGEN)

Include more linguistic phenomena

- Partial fronting phenomena
- Extraposed relative clauses
- Treatment of verbal complex
- Coordination and ellipsis
- Semantics

Lexicon

- More subcat frames
 - (Hand-written) list of all subcat frames present in the TüBa-D/Z treebank is available
- Larger Lexicon

Parsing

- restricting the formalism to keep/make it mildly context-sensitive
- transforming the MCTAG into a simple RCG for parsing